



Product No.	Dimensions																Weight (kg)	Load ratings, radial	
	d	D	T	A	B	C	D ₁	D _{a min}	D _{b min}	d _{a max}	d _{b max}	d _k	r _{1s min}	r _{2s min}	s	α		C _r (N)	C _{0r} (N)
GE25SX	25	47	15	7,5	14	14	31,4	34,0	43,0	30,1	39,5	42,5	0,6	0,2	1,0	2,7°	0,14	47.500	236.000
GE28SX	28	52	16	8,0	15	15	35,7	40,0	47,5	34,4	42,0	47,0	1,0	0,3	1,0	2,4°	0,18	57.500	287.000
GE30SX	30	55	17	8,5	16	16	36,1	40,5	50,5	34,6	45,0	50,0	1,0	0,3	2,0	2,3°	0,21	64.600	323.000
GE35SX	35	62	18	9,0	17	17	42,4	47,0	57,0	41,1	50,0	56,0	1,0	0,3	2,0	2,1°	0,27	76.500	390.000
GE40SX	40	68	19	9,5	18	18	46,8	52,0	61,0	45,5	54,0	60,0	1,0	0,3	1,5	1,9°	0,33	90.000	450.000
GE45SX	45	75	20	10,0	19	19	52,9	58,0	67,0	51,7	60,0	66,0	1,0	0,3	1,5	1,7°	0,42	106.000	530.000
GE50SX	50	80	20	10,0	19	19	59,1	65,0	75,0	57,9	67,0	74,0	1,0	0,3	4,0	1,6°	0,46	118.000	590.000
GE55SX	55	90	23	11,5	22	22	62,0	70,0	81,0	60,7	71,0	80,0	1,5	0,6	4,0	1,4°	0,68	146.000	735.000
GE60SX	60	95	23	11,5	22	22	68,1	76,0	87,0	66,9	77,0	86,0	1,5	0,6	5,0	1,3°	0,73	160.000	802.000
GE65SX	65	100	23	11,5	22	22	75,6	84,0	93,0	74,4	83,0	92,0	1,5	0,6	5,0	1,3°	0,77	173.000	865.000
GE70SX	70	110	25	12,5	24	24	82,2	90,0	104	80,9	92,0	102	1,5	0,6	7,0	1,1°	1,10	208.000	1.040.000
GE80SX	80	125	29	14,5	27	27	90,5	99,0	117	88,0	104	115	1,5	0,6	10	2,0°	1,50	250.000	1.250.000
GE90SX	90	140	32	16,0	30	30	103,3	112	132	100,8	118	130	2,0	0,6	11	1,8°	2,10	320.000	1.600.000
GE100SX	100	150	32	16,0	30	30	114,3	123	142	112,0	128	140	2,0	0,6	12	1,7°	2,30	339.000	1.690.000
GE110SX	110	170	38	19,0	36	36	125,8	135	162	123,2	146	160	2,5	0,6	15	1,5°	3,90	469.000	2.340.000
GE120SX	120	180	38	19,0	36	36	135,4	145	172	132,9	155	170	2,5	0,6	17	1,4°	4,00	498.000	2.490.000
GE130SX	130	200	45	22,5	42	42	148,0	158	192	143,9	174	190	2,5	0,6	20	1,9°	6,10	640.000	3.200.000
GE140SX	140	210	45	22,5	42	42	160,6	171	202	156,9	184	200	2,5	0,6	20	1,8°	6,50	680.000	3.450.000
GE150SX	150	225	48	24,0	45	45	170,9	184	216	167,1	194	213	3,0	1	21	1,7°	7,90	780.000	3.900.000
GE160SX	160	240	51	25,5	48	48	181,4	195	228	177,7	206	225	3,0	1	21	1,6°	9,60	872.000	4.360.000
GE170SX	170	260	57	28,5	54	54	194,3	208	253	190,4	228	250	3,0	1	27	1,4°	13,00	1.080.000	5.440.000
GE180SX	180	280	64	32,0	61	61	205,5	220	263	201,7	240	260	3,0	1	21	1,3°	17,50	1.310.000	6.590.000
GE190SX	190	290	64	32,0	61	61	211,8	226	278	207,9	252	275	3,0	1	29	1,3°	18,30	1.370.000	6.850.000
GE200SX	200	310	70	35,0	66	66	229,2	244	293	224,1	268	290	3,0	1	26	1,6°	23,30	1.560.000	7.800.000