

**Pyyhkijät
GHM**

NBR

NBR

	<p>Toleranssit: $\varnothing D: +0,2/0$ $h: +0,1/0$ Materiaali: NBR 90° Shore A Käyttöolosuhteet: Lämpötila: $-40\text{ °C} \dots +100\text{ °C}$ Nopeus : $<4\text{ m/s}$</p>
--	---

<u>Nimike</u>	<u>Materiaali</u>	<u>d</u>	<u>D</u>	<u>L</u>	<u>1 kpl</u>	<u>100 kpl</u>
GHM16/22X3X5	NBR	16,0	22,0	3,0	4,46	3,14
GHM30	NBR	30,0	38,6	5,3	5,34	3,76
GHM35	NBR	35,0	43,6	5,3	6,22	4,38
GHM45	NBR	45,0	55,6	5,3	6,84	4,82
GHM55	NBR	55,0	65,6	5,3	7,90	5,56
HL6-63	NBR	63,0	73,6	5,3	8,43	5,94
HL6-65	NBR	65,0	75,6	5,3	8,43	5,94
GHM75	NBR	75,0	87,2	7,1	12,89	9,08
GHM80	NBR	80,0	92,2	7,1	13,56	9,55
GHM110	NBR	110,0	122,2	7,1	18,48	13,02
GHM115	NBR	115,0	127,2	7,1	19,06	13,43
HLP6-140	NBR	140,0	155,0	10,1	40,15	28,28
HLP6-150	NBR	150,0	165,0	10,1	31,76	22,37
GHM200	NBR	200,0	220,2	10,1	56,09	39,50
HLP6-300	NBR	300,0	320,0	10,1	173,18	121,96
GHM340/360	NBR	340,0	360,0	10,1	246,61	173,67
HLP6-360	NBR	360,0	380,0	10,1	430,28	303,01