
















Axial deep groove ball bearings 512

main dimensions to DIN 711/ISO 104, single direction, separable



	d	D	T			
	mm	mm	mm			
51200	10	26	11			
51201	12	28	11			
51202	15	32	12			
51203	17	35	12			
51204	20	40	14			
51205	25	47	15			
51206	30	52	16			
51207	35	62	18			
51208	40	68	19			
51209	45	73	20			
51210	50	78	22			
51211	55	90	25			
51212	60	95	26			
51213	65	100	27			
51214	70	105	27			
51215	75	110	27			
51216	80	115	28			
51217	85	125	31			
51218	90	135	35			
51220	100	150	38			
	d	D	T			
	mm	mm	mm			
51222	110	160	38			
51224	120	170	39			
51226	130	190	45			
51228	140	200	46			
51230-MP	150	215	50			
51232-MP	160	225	51			
51234-MP	170	240	55			
51236-MP	180	250	56			
51238-MP	190	270	62			
51240-MP	200	280	62			
51244-MP	220	300	63			
51248-MP	240	340	78			
51252-MP	260	360	79			

51256-MP	280	380	80			
51260-MP	300	420	95			
51264-MP	320	440	95			
51268-MP	340	460	96			
51272-MP	360	500	110			
d	D	T				
mm	mm	mm				